

The logo for QIHANG, featuring the word "QIHANG" in a bold, blue, sans-serif font. The letter "I" is stylized with a red vertical bar on its right side. The logo is set against a white rectangular background.

QIHANG

Guangzhou Qihang Machinery & Equipment Co., Ltd

price list

Contact: 86+15626014514

TEL:+86-20-36524012 Valid date:30days Day:2020.6.5

Website Address:<http://www.cosmetic-makingmachine.com/>



Vacuum homogenizer emulsifier

真空均质乳化机

QH-G-ZRG-B 固定式内外循环真空均质乳化机
QH-G-ZRG-B Fixed type internal and external vacuum homogenizer emulsifier



QH-G-ZRG-A 固定式真空均质乳化机
QH-G-ZRG-A Fixed type vacuum homogenizer emulsifier



1000L-A vacuum homogeneous emulsifier

Number	Specification
1	Mixing method: 1. Frame-type wall scraping and stirring, power 7.5KW, rotation speed 0-60 RPM 2. Material of agitator: 316L stainless steel Polishing grade: the inside and outside parts of the pot are more than 300 mesh Discharging valve: 51mm stainless steel ball valve
2	Seal: Mechanical seal Open cover: pot cover sealed, manhole open cover Discharging mode: manual ball valve with diameter of 51mm discharging or pumping discharging Temperature display: Thermal resistance thermometer (less than or equal to 140 degrees)
3	Vacuum: Pressure vacuum gauge, vacuum gauge $\leq -0.08\text{mpa}$ Heating and cooling method: Steam heating water cooling
4	Capacity design: Designed volume 1100L, working volume 1000L Main process parameters: 1. Jacket working pressure: 0.25mpa 2. Working pressure of inner pot is -0.08-0.01mpa

Number	Specification
5	Material: 1. The inner pot is made of 316L stainless steel with a thickness of 6mm (GMP) 2. Jacket material SUS304 stainless steel, thickness of 5mm (GMP) 3. The shell is made of SUS304 stainless steel with a thickness of 2mm (GMP)
6	Upper pot cover material: 316L stainless steel, thickness of 5mm Vacuum pressure gauge, vent valve, vacuum port, view mirror lamp, view mirror port with scraper, spice funnel; Vacuum pump 4KW water ring vacuum pump, type 2BV, pumping speed 1220L/ min
7	Material piping: All parts contacting with material are made of 316L stainless steel Spice bucket made of stainless steel, quantity: 1 set Polishing grade: the inside and outside parts of the pot are more than 300 mesh Discharging valve: 51mm stainless steel ball valve;
8	Tank structure tank body is three-layer, sealed vacuum tank body, heating with external insulation device, lower oval head, tank body in the center with paddle stirring, pipe mouth, view mirror, valve outlet at the bottom, temperature probe

Electric control cabinet

Number	Specification
1	Shell material: SUS304 stainless steel plate, plate thickness is 2mm Dimensions: 800mm wide * 1700mm high * 310mm deep (W*H*L)
2	Meter: current voltmeter, thermometer, time digital display meter, inverter panel
3	Button part: each function control button, power display light, emergency stop, etc Electrical components: include control relays

Power consumption

1000L vacuum stirring pot:	Frame wall scraping stirring power: 7.5KW. Homogenizer power: 11KW. Steam heating
water ring vacuum pump	Power: 4 kw

With the shipment prices to Zimbabwe

- Guangzhou to Bulawayo train price
- Ocean freight: USD305/CBM
- Documentation fee: USD42/BL
- Weighing fee: USD21/BL
- Date of shipment: one ship will leave next Monday, which is pre-arranged by PIL and will transit to Durban. It is expected to arrive in 50 days
- Destination port charges:

DESTINATION CHARGES	
DURBAN CHARGES	
DEGROUP (PER W/M)	\$49.00
CARGO DUES (PER W/M)	\$20.00
RELEASE FEE	\$80.00
DOCUMENTATION	\$20.00
COMMUNICATIONS	\$10.00
UNPACKING (PER W/M)	\$40.00
GATE PASS PER SHIPMENT	\$5.00
	\$0.75
STORAGE (PER W/M /DAY IF APPLICABLE , MIN \$40 PER MONTH)	

